Elpro.com.pl: ul. Legionów 93/95, 91-072 Łódź
www: www.elpro.com.pl **e-mail**: sklep_www@elpro.com.pl **tel**: (42) 664-06-00

POINDUS TERMINAL DOTYKOWY VARIPOS S 715S



Produkt jest niedostępny

Kategorie Terminale dotykowe

Poindus

Model Name		VariPOS 715S	VariPOS 8
Main Board	CPU	Intel® Celeron J1900 quad-core 2.0GHz with L2 Cache 2MB (Fanless)	Intel® Celeron 1037U dual-core 1.8GHz 3rd Gen Intel® Core i3-3217U dual-core
	Chipset	CPU Integrated	Intel® PCH HM76
	System Memory	1 x DDR3 SO-DIMM up to 8GB	
Display	TFT LCDItd>	15" TFT LCD(LED backlight)	
	Brightness	250nits	
	Resolution	1024 x 768	
	Touch Screen	True Flat Projected Capacitive Technology / True Flat 5-Wire Resistive	
Storage	HDD / SSD Type	1 x SATA (2.5") HDD or SSD	
I/O Ports -External	DC Input	1 x Mini Din 4P (DC 19V only)	
	Cash Drawer	1 x RJ-11 (12V or 24V(default))	
	Network (LAN)	1 x Gigabit Ethernet by RJ-45	
	USB Port	2 x USB 2.0 / 1 x USB 3.0	2 x USB 2.0 / 2 x USB 3.0
	Serial Port	1 x RS-232(RJ45 connector) (COM1/COM2/by COM3(12V), COM4(12V) Power enabled by BIOS setting (default disable))	
	POWER ON/OFF	1 x power on/off switch button	
	VGA Port	1 x DB-15 VGA Port	
I/O Ports -Internal	Card Reader & iButton	1XOM6 : Internal Pin header for Card Reader & iButton	
	Audio	HD Audio, 2W Speaker x 2	
	Bus Expansion	1 x Mini-PCI-E Slot	
Compliance		IP 66 on front panel (Front Panel)	
System Management		Desktop Management Interface (DMI)	
		Preboot Execution Environment (PXE)	
		Wake on LAN (WoL)	
		Advanced Configuration and Power Interface (ACPI)	
OS Support		Windows 7, POSready 7	
Power Supply		External adapter DC Model: 65 Watts Voltage: +19VDC 3.42A max.	
Material		Main Unit: Die-casting aluminum ; I/O Cover:Plastic	
Color		Main Unit: Black	
Certifications		CE, FCC, RoHS	
Dimension(W x H x D)		370 x 300 x 236 mm	
Weight		5.68 Kg	
Operating Temperature		0°C ~ 40°C, 10% ~ 90% RH, non-condensing	

Storage Temperature		-30°C ~ 60°C, 10% ~ 90% RH, non-condensing
Optional Accessories		
-	VFD	2 x 20 attached VFD
-	MSR	Front, 3 tracks RS-232 Type or PS/2 Type
-	MSR & iButton	MSR-Front & iButton, RS-232 Type or PS/2 Type
-	Fingerprint Reader	USB
-	RFID	USB, 13.56MHZ Read / Write
-	7" 2nd display	Resolution 800 x 600
-	10.4" 2nd display	Resolution 800 x 600

Wersja produktu	Cena

DANE TECHNICZNE	
PROCESOR	Intele Celeron J1900 quad-core 2.0GHz (2MB Cache)
CHIPSET	Zintegrowany CPU
PAMIĘĆ RAM	1 x DDR3 SO-DIMM up to 8GB
SYSTEMY OPERACYJNE (OPCJE)	Windows 7, POSready 7
PORTY KOMUNIKACYJNE	1xMini Din 4P (DC 19V only), 1xRJ-11, 1xGigabit Ethernet by RJ-45, 4xUSB 2.0, 1xUSB 3.0, 3xRS-232, 1xDB-15 VGA Port, 1xMini-PCI-E Slot
TWARDY DYSK	1 x SATA 2,5" HDD or SSD
KOLOR OBUDOWY	czarny lub jasny
MONITOR	15" LED Backlight
PRZEKĄTNA EKRANU	15"
WYMIARY	370 x 300 x 236 mm
WAGA	5,68 kg
ROZDZIELCZOŚĆ NATYWNA	1024 x 768
JASNOŚĆ PANELA LCD	250nits
DOPUSZCZALNE TEMPERATURY I WILGOTNOŚĆ	Temp. przechowywania -20 ~ 60 stopni C., Temp. pracy 0 ~ 40 stopni C. , Wilgotność 20 ~ 90%
ZASILACZ	Zewnętrzny zasilacz, DC Model:65 Watów, Napięcie:+19VDC 3,42A max

Galeria








